

The sliding and folding door range with all the answers



- Can your doors easily meet all the requirements of Document L?
- Can the leaf heights go up to 3 m?
- Can they be in single or dual colour frames?
- Can you offer a burglar resistance option to EN V 1627 Class 2?
- Can your sliding doors have single, double or triple tracks?
- Can your folding doors offer you a flush threshold option only 3.5 mm high?
- Can the outer frame width be adjusted after installation?

Because Schueco's can!

To discover the benefits of becoming a Schueco partner
contact us today on 01908 282111 or email mkinfobox@schueco.com



Green Technology for the Blue Planet
Clean Energy from Solar and Windows

SCHÜCO

Versatility is built-in with Schueco



Just some of the reasons for using Schueco's sliding and folding doors:

Folding doors

- U values as low as 1.3 W/m²K
- Narrow sight lines down to 112 mm
- Maximum leaf size up to 1.2 m wide x 3 m high
- Leaf weights up to 100 kg
- Glazing units up to 53 mm thick for ultimate heat saving
- Outer frame width can be adjusted after installation
- Single or dual colour frames
- Flush threshold option only 3.5 mm high is available
- Finger-safe gaskets
- Choice of stainless steel multi-point locks provide secure locking
- Intermediate leaves can be key locked for greater security
- Burglar resistance option to EN V 1627 Class 2
- All frames are mitre cut for strong joints and ease of fabrication

Sliding doors

- U values as low as 1.3 W/m²K
- Maximum leaf height 3 m, maximum width 3 m
- Glass thickness up to 52 mm
- Single, double or triple tracks
- Single or dual colour frames
- Choice of handle finishes including stainless steel
- Burglar resistance option to EN V 1627 Class 2

To discover the benefits of becoming a Schueco partner contact us today on 01908 282111 or email mkinfobox@schueco.com

April 2011